

LUBING
POULTRYTEC



**SLOPE REGULATOR
FOR REARING
AND FINISHING**



THE LUBING SLOPE REGULATOR

The valve of the slope regulator will remain open until the pressure in the drinking line has reached the predetermined level. If this level is reached, the valve closes automatically and keeps the water column consistently and safely at the desired level. The adjustable slope regulator compensates variable a height difference of 10-45 cm.



SELECTION AND VERSIONS

		Transition pieces from the slope regulator to: 22 mm square pipe Art. No. 3303-00			Transition pieces from the slope regulator to: 28 mm square pipe Art. No. 3304-00		
		Breather unit			Breather unit		
		6	7	8	6	7	8
Hanger		450 mm	600 mm	900 mm	450 mm	600 mm	900 mm
3	Aluminum profile	3242-00	3242-6-00	3242-9-00	-	-	-
4	Turkey profile	-	-	-	3243-00	3243-6-00	3243-9-00
5	Round pipe Ø 25,4 and 26,7 mm	3244-00	3244-6-00	3244-9-00	3245-00	3245-6-00	3245-9-00

Max. 2 slope regulators in one watering line.



LUBING

POULTRYTEC

LUBING Maschinenfabrik GmbH & Co. KG
Lubingstraße 6 | 49406 Barnstorf
Germany

T +49 (0) 54 42 98 79 - 0
F +49 (0) 54 42 98 79 - 33
M info@lubing.de

LUBING.COM

As of: May 2026 | We reserve the right to make technical changes, further developments and improvements.
No. 0829-1