

# LUBING

STABLETEC

## LUBING TOUCH CONTROL FOR LUBING SYSTEM SOLUTIONS



# LUBING TOUCH CONTROL

All LUBING Touch Controllers are characterized by their intelligent systematics and intuitive operability. Supply and maintenance processes in the house are controlled automatically via simple touch fields with pictograms. Important and daily functions are integrated as direct functions, less important and administrative functions are outsourced to lower-level menus. Depending on the house system and the LUBING system used, the LUBING Touch Controllers are available in many different versions tailored to the desired application.

## MENU PICTOGRAMS



On/Off



Menu



Dust binding



Home



Automatic



Timer

## VERSIONS

The LUBING Touch Controllers are offered in many versions. The designation of the version starting with LC is noted on the front foil.

Description	Art.no.	Application in Top Climate Systems
LC-1	Art. 7740	1-house systems without sensors
LC-2	Art. 7741	2-house systems without sensors
LCS-1	Art. 7742	1-house systems with sensors
LCS-2	Art. 7743	2-house systems with sensors
LCM	Art. 7744	Multi-compartment control for max. 8 compartments
LCM vario	Art. 7745	Multi compartment control for max. 8 compartments for pump units with frequency converter
Extension box LCM/LCMvario	Art. 7750	Extension for LCM and LCM Vario by 8 compartments (max. 4 extension boxes per controller)
LCMS Vario	Art. 7747	Multi compartment control for max. 2 compartments for pump units
Extension box LCMS Vario	Art. 7751	Extension for LCMS Vario by 2 compartments (max. 14 extension boxes per controller)

These versions are designed for a wide voltage range of 90 to 264 V 50/60 Hz mains voltages.

## ➤ ADVANTAGES

- » Interactive touch display with status messages and context-sensitive menu navigation.
- » Logically structured, step-by-step operator processes in ergonomically designed interface.
- » Integrated alarm functions for critical conditions and to protect against operating errors.
- » Hierarchical menu structure: quick access to the most frequently used functions.
- » Control of several lines / houses via one device.
- » Extension of operating functions via CANBus.
- » Extension sets for the control of additional lines.
- » Regular updates (via SD card).
- » Data logging (optional).

# LUBING

STABLETEC

LUBING Maschinenfabrik GmbH & Co. KG  
Lubingstraße 6 | 49406 Barnstorf  
Germany

T +49 (0) 54 42 98 79 - 0  
F +49 (0) 54 42 98 79 - 33  
M info@lubing.de

**LUBING.COM**

As of: May 2026 | We reserve the right to make technical changes, further developments and improvements.  
No. 0844-1