

LUBING
POULTRYTEC

**ACCUMULATOR
TABLE
FOR
CONVEYOR SYSTEMS**





➤ ADVANTAGES

- » corrosion-resistant stainless steel frame with integrated height adjustment from 830 to 1,110 mm
- » modular plastic elements with hinge joints
- » table dimensions (length and width) can be adjusted according to customer requirements
- » belt speed: 5.3 meters/minute
- » guide angles up to 22° ensure gentle delivery of the eggs
- » reduction of broken eggs due to integrated jam switches
- » drive by the proven flat gear motors of the LUBING conveyor systems (0.37 kW, special voltages on request)

TECHNICAL DATA



01

Plastic mat

Flexible and robust plastic mat with modular structure. The individual elements of the plastic mat have been optimized for easy cleaning.



02

Guide units

Due to the guide units with length adjustment, different inlet and outlet widths can be easily realized.



03

Jam switch

The integrated jam switch monitors the filling level of the metering table during operation. In case of an overload, the feeding belts are stopped automatically to protect the eggs.



04

Frame

The frame of the accumulator table consists of solid square tubes, which are screwed together with stable angles.



05

Height adjustment

Precise height adjustment of the frame by integrated threaded spindles.

LUBING

POULTRYTEC

LUBING Maschinenfabrik GmbH & Co. KG
Lubingstraße 6 | 49406 Barnstorf
Germany

T +49 (0) 54 42 98 79 - 0
F +49 (0) 54 42 98 79 - 33
M info@lubing.de

LUBING.COM